

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

# wattyl®

A part of  HEMPEL

Conforms to Model Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals - Australia

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE  
Product identity : 160909  
Product type : Paint or paint related material

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings  
Identified uses : Consumer applications, Professional applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) Australia Pty Ltd.  
Level 3, 2 Burbank Place  
Norwest, , New South Wales 2153  
Australia  
Tel: +(61) 288673333  
Email: wattyl@wattyl.com.au

Date of Preparation : 16 December 2024  
Date of previous issue : 5 December 2024.

#### 1.4 Emergency telephone number


Emergency telephone number (with hours of operation)  
  
Poisons Information Centre.  
Tel.: 13 11 26 (24 hour)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### GHS Classification


 FLAMMABLE LIQUIDS - Category 2  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
SKIN SENSITISATION - Category 1  
CARCINOGENICITY - Category 1  
REPRODUCTIVE TOXICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

#### 2.2 Label elements

Hazard pictograms :



Signal word : DANGER

Hazard statements :  H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H336 - May cause drowsiness or dizziness.  
H350 - May cause cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor, mist or spray. Wash thoroughly after handling.  
Response : IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.


# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 2: Hazards identification

Storage :  Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Not applicable.

#### 2.3 Other hazards

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%
toluene	CAS: 108-88-3	≥10 - ≤30
n-butyl acetate	CAS: 123-86-4	≤10
xylene	CAS: 1330-20-7	≤10
solvent naphtha (petroleum), light aliph.	CAS: 64742-89-8	≤5
butan-1-ol	CAS: 71-36-3	≤5
2-(2-butoxyethoxy)ethanol	CAS: 112-34-5	≤3
ethylbenzene	CAS: 100-41-4	≤3
2-methoxy-1-methylethyl acetate	CAS: 108-65-6	≤3
2-methylpropan-1-ol	CAS: 78-83-1	≤3
formaldehyde	CAS: 50-00-0	≤0.3

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.

Skin contact : Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

##### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:  
pain  
watering  
redness

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 4: First aid measures

Inhalation :	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact :	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	If gasses have been inhaled, from the decomposition of the product, symptoms may be delayed. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray. Not to be used : waterjet.
-----------------------	--

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
---	---

Hazardous combustion products : Decomposition products may include the following materials: carbon oxides nitrogen oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Hazchem code : ●3YE

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 6: Accidental release measures

#### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spill product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Product/ingredient name	Exposure limit values
toluene	<b>Safe Work Australia (Australia, 1/2024)</b> Absorbed through skin. STEL 15 minutes: 574 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. TWA 8 hours: 191 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
n-butyl acetate	<b>Safe Work Australia (Australia, 1/2024)</b> STEL 15 minutes: 950 mg/m <sup>3</sup> . STEL 15 minutes: 200 ppm. TWA 8 hours: 713 mg/m <sup>3</sup> . TWA 8 hours: 150 ppm.
xylene	<b>Safe Work Australia (Australia, 1/2024) [Xylene (o-, m-, p- isomers)]</b> STEL 15 minutes: 655 mg/m <sup>3</sup> . STEL 15 minutes: 150 ppm. TWA 8 hours: 350 mg/m <sup>3</sup> . TWA 8 hours: 80 ppm.
solvent naphtha (petroleum), light aliph.	<b>Safe Work Australia (Australia, 1/2024) [Hexane, other isomers]</b> STEL 15 minutes: 3500 mg/m <sup>3</sup> . STEL 15 minutes: 1000 ppm. TWA 8 hours: 1760 mg/m <sup>3</sup> . TWA 8 hours: 500 ppm.
butan-1-ol	<b>Safe Work Australia (Australia, 1/2024)</b> Absorbed through skin. PEAK: 50 ppm. PEAK: 152 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	<b>ACGIH TLV (United States, 1/2024)</b> TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor.
ethylbenzene	<b>Safe Work Australia (Australia, 1/2024)</b> STEL 15 minutes: 543 mg/m <sup>3</sup> . STEL 15 minutes: 125 ppm. TWA 8 hours: 434 mg/m <sup>3</sup> .

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 8: Exposure controls/personal protection

2-methoxy-1-methylethyl acetate	TWA 8 hours: 100 ppm. <b>Safe Work Australia (Australia, 1/2024)</b> Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. STEL 15 minutes: 548 mg/m <sup>3</sup> .
2-methylpropan-1-ol	<b>Safe Work Australia (Australia, 1/2024)</b> TWA 8 hours: 152 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm.
formaldehyde	<b>Safe Work Australia (Australia, 1/2024)</b> Carc. 2. Sensitiser. STEL 15 minutes: 2.5 mg/m <sup>3</sup> . STEL 15 minutes: 2 ppm. TWA 8 hours: 1.2 mg/m <sup>3</sup> . TWA 8 hours: 1 ppm.

#### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the workstation location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection :

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton®

May be used: nitrile rubber (>0.3 mm), butyl rubber (>0.5 mm)

Short term exposure: neoprene rubber (>0.1 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

Body protection :

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

Wear suitable protective clothing.

Chemical-resistant apron.

Respiratory protection :

When the product is applied by spraying and for continuous or prolonged work always wear an air-fed respirator e.g. hood with supply of fresh or compressed air or a full face, powered air purifying filter.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. Be sure to use an approved/certified respirator or equivalent.

#### Environmental exposure controls

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 8: Exposure controls/personal protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state :	Liquid.
Odour :	Solvent-like
pH :	Testing not relevant or not possible due to nature of the product.
Melting point/freezing point :	Testing not relevant or not possible due to nature of the product.
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.
Flash point :	Closed cup: -15°C (5°F)
Evaporation rate :	Testing not relevant or not possible due to nature of the product.
Flammability :	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidising materials.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Toluene	23.17	3.1		90	12	

Vapour density : Not available.

Specific gravity : 1.02 g/cm<sup>3</sup>

Partition coefficient (LogKow) : Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
pigment yellow 151	320	608	

Decomposition temperature : Testing not relevant or not possible due to nature of the product.

Viscosity : Testing not relevant or not possible due to nature of the product.

Explosive properties : Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidising materials.  
Slightly explosive in the presence of the following materials or conditions: reducing materials.

Oxidising properties : Testing not relevant or not possible due to nature of the product.

#### 9.2 Other information

Solvent(s) % by weight :	Weighted average: 46 %
Water % by weight :	Weighted average: 0 %
VOC content :	465.9 g/l
TOC Content :	Weighted average: 377 g/l
Solvent Gas :	Weighted average: 0.116 m <sup>3</sup> /l

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

### SECTION 10: Stability and reactivity

#### 10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidising materials.  
Reactive or incompatible with the following materials: reducing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides nitrogen oxides

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Direct contact with the eyes can cause irreversible damage, including blindness.

#### Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
toluene	Rat - Oral - LD50	636 mg/kg	Toxic effects: Eye - Corneal damage Cardiac - Pulse rate Lung, Thorax, or Respiration - Dyspnea Toxic effects: Liver - Fatty liver degeneration Kidney, Ureter, and Bladder - Other changes Blood - Other changes  Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes  Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes  Toxic effects: Behavioral - Tremor Liver - Other changes Kidney, Ureter, and Bladder - Other changes
n-butyl acetate	Rat - Inhalation - LC50 Vapour	>20 mg/l [4 hours]	
xylene	Rat - Oral - LD50	10768 mg/kg	
	Rabbit - Dermal - LD50	>14112 mg/kg	
butan-1-ol	Rat - Inhalation - LC50 Vapour	>21 mg/l [4 hours]	
	Rabbit - Dermal - LD50	>4200 mg/kg	
2-(2-butoxyethoxy)ethanol	Rat - Oral - LD50	3523 mg/kg	
	Rat - Inhalation - LC50 Vapour	6350 ppm [4 hours]	
ethylbenzene	Rat - Inhalation - LC50 Gas.	5000 ppm [4 hours]	
	Rabbit - Dermal - LD50	3400 mg/kg	
2-methoxy-1-methylethyl acetate	Rat - Oral - LD50	790 mg/kg	
	Rat - Inhalation - LC50 Vapour	24000 mg/m <sup>3</sup> [4 hours]	
2-methylpropan-1-ol	Rat - Oral - LD50	4500 mg/kg	
	Rabbit - Dermal - LD50	2700 mg/kg	
formaldehyde	Rat - Oral - LD50	3500 mg/kg	
	Rabbit - Dermal - LD50	>5000 mg/kg	
formaldehyde	Rabbit - Dermal - LD50	>5 g/kg	
	Rat - Oral - LD50	8532 mg/kg	
	Rat - Oral - LD50	2460 mg/kg	
	Rabbit - Dermal - LD50	3400 mg/kg	
formaldehyde	Rat - Inhalation - LC50 Vapour	19200 mg/m <sup>3</sup> [4 hours]	
	Rabbit - Dermal - LD50	270 mg/kg	
	Rat - Oral - LD50	100 mg/kg	
	Rat - Inhalation - LC50 Gas.	250 ppm [4 hours]	
formaldehyde	Rat - Male, Female - Inhalation - LC50 Vapour	0.58 mg/l [4 hours]	

#### Acute toxicity estimates

Route	ATE value
Oral	24272.67 mg/kg
Dermal	20779.31 mg/kg
Inhalation (gases)	75218.58 ppm
Inhalation (vapours)	902.96 mg/l

#### Irritation/Corrosion

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

### SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Exposure
toluene	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 0.5 minutes	Amount/concentration applied: 100 mg
	Rabbit - Skin - Moderate irritant		Amount/concentration applied: 20 mg
n-butyl acetate	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 500 mg
	Rabbit - Eyes - Mild irritant		
xylene	Rabbit - Respiratory - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 5 milligrams
	Rabbit - Eyes - Severe irritant		Amount/concentration applied: 500 milligrams
butan-1-ol	Rabbit - Skin - Irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 2 milligrams
	Rabbit - Eyes - Severe irritant		Amount/concentration applied: 20 milligrams
2-(2-butoxyethoxy)ethanol	Rabbit - Skin - Moderate irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 20 milligrams
	Rabbit - Eyes - Severe irritant		Amount/concentration applied: 20 milligrams
ethylbenzene	Rabbit - Skin - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 15 milligrams
	Rabbit - Respiratory - Mild irritant		
2-methoxy-1-methylethyl acetate	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	
	Rabbit - Respiratory - Mild irritant		
2-methylpropan-1-ol	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	
	Rabbit - Skin - Irritant		
formaldehyde	Rabbit - Skin - Irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 750 ug
	Rabbit - Eyes - Severe irritant		
	Human - Skin - Mild irritant		Amount/concentration applied: 150 ug l
	Rabbit - Skin - Moderate irritant		Amount/concentration applied: 50 mg
	Rabbit - Skin - Severe irritant	Duration of treatment/ exposure: 20 hours	

#### Sensitiser

Product/ingredient name	Species - Route of exposure	Result
formaldehyde	Guinea pig - skin Mouse - skin	Result: Sensitising Result: Sensitising

#### Mutagenic effects

No known data available in our database.

#### Carcinogenicity

No known data available in our database.

#### Reproductive toxicity

No known data available in our database.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
toluene	Category 3		Narcotic effects
n-butyl acetate	Category 3		Narcotic effects
solvent naphtha (petroleum), light aliph.	Category 3		Narcotic effects
butan-1-ol	Category 3		Respiratory tract irritation
2-methoxy-1-methylethyl acetate	Category 3		Narcotic effects
2-methylpropan-1-ol	Category 3		Narcotic effects
	Category 3		Respiratory tract irritation
formaldehyde	Category 3		Narcotic effects
	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

### SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
toluene ethylbenzene	Category 2 Category 2		hearing organs

#### Aspiration hazard

Product/ingredient name	Result
toluene solvent naphtha (petroleum), light aliph. ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

#### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

No known significant effects or critical hazards.

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Harmful to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
toluene	Chronic - NOEC - Fresh water Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	1000 µg/l [21 days] <500000 µg/l [96 hours]
n-butyl acetate	Acute - EC50	Daphnia	44 mg/l [48 hours]
butan-1-ol	Acute - EC50 Acute - LC50	Algae Fish	648 mg/l [72 hours] 1.376 mg/l [96 hours]
2-(2-butoxyethoxy)ethanol	Acute - EC50 Acute - LC50	Daphnia Algae Fish	1328 mg/l [96 hours] 100 mg/l [96 hours] 1300 mg/l [96 hours]
ethylbenzene	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	<1000 µg/l [96 hours]
2-methoxy-1-methylethyl acetate	Acute - LC50	Fish	100 - 180 mg/l [96 hours]
2-methylpropan-1-ol	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	4000 µg/l [21 days]
formaldehyde	Chronic - NOEC - Marine water	Algae - Green algae - <i>Ulva pertusa</i>	0.438 mg/l [96 hours]

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result
toluene n-butyl acetate	OECD Ready Biodegradability - Closed Bottle Test	100% [14 days] - Readily 90% [28 days] - Readily
xylene	OECD Ready Biodegradability - Manometric Respirometry Test	80% [5 days] - Readily >60% [28 days] - Readily
butan-1-ol ethylbenzene	OECD Ready Biodegradability - Closed Bottle Test	90 - 98% [28 days] - Readily
2-methoxy-1-methylethyl acetate	OECD Ready Biodegradability - Manometric Respirometry Test	92% [20 days] >70% [28 days] - Readily
	OECD Ready Biodegradability - Manometric Respirometry Test	83% [28 days] - Readily
formaldehyde	OECD Ready Biodegradability - DOC Die-Away Test	90% [28 days] - Readily 99% [28 days] - Readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene n-butyl acetate xylene butan-1-ol ethylbenzene 2-methoxy-1-methylethyl acetate formaldehyde			Readily Readily Readily Readily Readily Readily Readily

#### 12.3 Bioaccumulative potential

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
toluene	2.73	90	Low
n-butyl acetate	2.3	3.1	Low
xylene	3.12	8.1 - 25.9	Low
solvent naphtha (petroleum), light aliph.	-	10 - 2500	High
butan-1-ol	1	3.16	Low
2-(2-butoxyethoxy)ethanol	1	-	Low
ethylbenzene	3.6	-	Low
2-methoxy-1-methylethyl acetate	1.2	-	Low
2-methylpropan-1-ol	1	-	Low
formaldehyde	0.35	3	Low

### 12.4 Mobility in soil

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
toluene	2.07	117.115
n-butyl acetate	1.52	33.2139
xylene	1.59	39
butan-1-ol	0.51	3.22078
2-(2-butoxyethoxy)ethanol	1.56	36.5981
ethylbenzene	2.23	170.406
2-methoxy-1-methylethyl acetate	0.36	2.31363
2-methylpropan-1-ol	1.08	12.0246
2-dimethylaminoethanol	1.65	44.8862
n-hexane	2.22	165.951
formaldehyde	1.57	37

Mobility : No known data available in our database.

### Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods




The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

#### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation ADG for transport by road and train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env* Additional information
<b>ADG Class</b>	UN1263	PAINT	3 	II	No. -
<b>IMDG Class</b>	UN1263	PAINT	3 	II	No. <u>Emergency schedules</u> F-E, S-E
<b>IATA Class</b>	UN1263	PAINT	3 	II	No. -

PG\* : Packing group

Env.\* : Environmental hazards

### 14.6 Special precautions for user

# Safety Data Sheet

## HIGH BAKE ENAMEL 609 NEW YELLOW TINTING BASE

wattyl®

A part of  HEMPEL

### SECTION 14: Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture


Standard for the Uniform Scheduling of Medicines and Poisons


Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

Ingredient name	Schedule
No listed substance	

### SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Classification	Justification
 FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SKIN SENSITISATION - Category 1 CARCINOGENICITY - Category 1 REPRODUCTIVE TOXICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.