

HSNO 2017 - New Zealand

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : EPINAMEL UHB1000 NEUTRAL GREY, PART A
Product identity : 200305
Product type : Paint or paint related material

1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings
Identified uses : Consumer applications, Professional applications, Used by spraying.

1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) New Zealand Limited
4-14 Patiki Road
Avondale, Auckland 1026
New Zealand
Tel.: +(64) 98010034
Email: wattyl@wattyl.com.au

Date of Preparation : 19 May 2025
Date of previous issue : 13 March 2025.

1.4 Emergency telephone number

Emergency telephone number (with hours of operation)

Poisons Centre New Zealand: 0800 764 766 (24 hour)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

GHS Classification

SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITISATION - Category 1
REPRODUCTIVE TOXICITY - Category 1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H360 - May damage fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand. Do not apply directly into or onto water. Take all reasonable steps to ensure that the substance does not cause any significant adverse effects to the environment beyond the application area.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid release to the environment. Do not breathe vapor, mist or spray. Wash thoroughly after handling.

Response : Collect spillage. IF exposed or concerned: Get medical advice or attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

SECTION 2: Hazards identification

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 dibutyl phthalate 4-nonylphenol, branched oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	CAS: 1675-54-3 CAS: 84-74-2 CAS: 84852-15-3 CAS: 68609-97-2 CAS: 220926-97-6	≥30 - ≤60 ≤10 <5 ≤5 ≤3

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
 If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

Inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.

Skin contact : Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
 pain
 watering
 redness

Inhalation : Adverse symptoms may include the following:
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

SECTION 4: First aid measures

Skin contact :	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments :	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Extinguishing media :	Recommended: alcohol resistant foam, CO ₂ , powders, water spray. Not to be used : waterjet.
-----------------------	--

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :	In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. This material may cause endocrine disruption in the environment. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products :	Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Contains epoxy constituents. Avoid all possible skin contact with epoxy and amine containing products, they may cause allergic reactions. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Product/ingredient name	Exposure limit values
dibutyl phthalate	HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023) WES-TWA 8 hours: 0.58 mg/m ³ . WES-TWA 8 hours: 0.05 ppm.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection :

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), butyl rubber (>0.5 mm), Viton®

May be used: nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

Short term exposure: neoprene rubber (>0.1 mm), natural rubber (latex) (>0.4 mm), polyvinyl alcohol (PVA), polyvinyl chloride (PVC)

SECTION 8: Exposure controls/personal protection

- Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.
Wear suitable protective clothing.
Chemical-resistant apron.
- Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. (EN140) Be sure to use an approved/certified respirator or equivalent.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : Liquid.
- Odour : Amine-like.
- pH : Testing not relevant or not possible due to nature of the product.
- Melting point/freezing point : Testing not relevant or not possible due to nature of the product.
- Boiling point/boiling range : Testing not relevant or not possible due to nature of the product.
- Flash point : Closed cup: 148°C (298.4°F)
- Evaporation rate : Testing not relevant or not possible due to nature of the product.
- Flammability : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
dibutyl phthalate	0.00007	0.0000093				

Vapour density : Not available.

Specific gravity : 1.51 g/cm³

Partition coefficient (LogKow) : Testing not relevant or not possible due to nature of the product.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
dibutyl phthalate	402	755.6	DIN 51794

Decomposition temperature : Testing not relevant or not possible due to nature of the product.

Viscosity : Testing not relevant or not possible due to nature of the product.

Explosive properties : Testing not relevant or not possible due to nature of the product.

Oxidising properties : Testing not relevant or not possible due to nature of the product.

9.2 Other information

- Solvent(s) % by weight : Weighted average: 1 %
- Water % by weight : Weighted average: 0 %
- VOC content : 11 g/l
- TOC Content : Weighted average: 8 g/l
- Solvent Gas : Weighted average: 0.004 m³/l

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

No specific data.

10.5 Incompatible materials

Reactive or incompatible with the following materials: oxidising materials and acids.

Slightly reactive or incompatible with the following materials: reducing materials.

10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Epoxy and amine containing products can cause skin disorders such as allergic eczema. The allergy may arise after only a short exposure period.

Direct contact with the eyes can cause irreversible damage, including blindness.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure	Effects
Bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Rat - Oral - LD50	>2000 mg/kg	
	Rabbit - Dermal - LD50	>2000 mg/kg	
dibutyl phthalate	Rat - Dermal - LD50	>2000 mg/kg	
	Rat - Oral - LD50	7499 mg/kg	
	Rabbit - Dermal - LD50	>20000 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	>15.68 mg/l [4 hours]	
4-nonylphenol, branched	Rat - Oral - LD50	1246 mg/kg	
	Rabbit - Dermal - LD50	>2000 mg/kg	
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Rat - Oral - LD50	>5000 mg/kg	
	Rat - Dermal - LD50	>4500 mg/kg	
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Rat - Oral - LD50	2000 mg/kg	
	Rat - Dermal - LD50	2000 mg/kg	
	Rat - Dermal - LD50	2000 mg/kg	
	Rat - Inhalation - LC50 Dusts and mists	3.56 mg/l [4 hours]	

Acute toxicity estimates

Route	ATE value
Oral	29590.97 mg/kg
Inhalation (vapours)	636.28 mg/l

Irritation/Corrosion

A

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Exposure
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Rabbit - Eyes - Mild irritant	Duration of treatment/ exposure: 24 hours	Amount/concentration applied: 100 milligrams Amount/concentration applied: 500 milligrams Duration of treatment/exposure: 24 hours
4-nonylphenol, branched	Rabbit - Skin - Mild irritant Rabbit - Eyes - Severe irritant		
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Rabbit - Skin - Severe irritant		
	Rabbit - Eyes - Mild irritant		
	Rabbit - Skin - Moderate irritant		

Sensitiser

Product/ingredient name	Species - Route of exposure	Result
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Guinea pig - skin	Result: Sensitising
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Guinea pig - skin	Result: Sensitising

Mutagenic effects

No known data available in our database.

Carcinogenicity

No known data available in our database.

Reproductive toxicity

No known data available in our database.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Not available.			

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Category 2	-	-
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
Not available.	

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential chronic health effects

No known significant effects or critical hazards.

Other information :

No additional known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Do not allow to enter drains or watercourses. Very toxic to aquatic life with long lasting effects.

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Acute - EC50	Algae	11 mg/l [72 hours]
	Acute - LC50	Fish	2 mg/l [96 hours]
dibutyl phthalate	Acute - EC50	Daphnia	1.8 mg/l [48 hours]
	Acute - EC50 - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	2990 µg/l [48 hours]
	Acute - LC50 - Fresh water	Fish - Bluegill - <i>Lepomis macrochirus</i> - Juvenile (Fledgling, Hatchling, Weanling)	480 µg/l [96 hours]
	Chronic - NOEC - Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	500 µg/l [21 days]
4-nonylphenol, branched	Acute - EC50 - Marine water	Algae - Dinoflagellate - <i>Gymnodinium breve</i>	3.4 µg/l [96 hours]
	Chronic - NOEC - Fresh water	Fish - Zebra danio - <i>Danio rerio</i> - Embryo	25 µg/l [5 weeks]
	Chronic - NOEC - Fresh water	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>	210 µg/l [96 hours]
	Chronic - NOEC - Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i> - Embryo	23 µg/l [33 days]
	Acute - LC50	Fish	0.128 mg/l [96 hours]
	Acute - EC50	Daphnia	0.085 mg/l [48 hours]
	Acute - EC50	Algae	0.0563 mg/l [72 hours]
	Acute - IC50	Algae	843.75 mg/l [72 hours]
oxirane, mono[(C12-14-alkyloxy) methyl] derivs.	Acute - LC50	Fish	5000 mg/l [96 hours]
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	Acute - LC50	Fish	>100 mg/l [96 hours]
	Acute - EC50	Daphnia	>100 mg/l [48 hours]
	Acute - EC50	Aquatic plants	>100 mg/l [72 hours]
	Acute - NOEC	Aquatic plants	100 mg/l [72 hours]

12.2 Persistence and degradability

Product/ingredient name	Test	Result
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 oxirane, mono[(C12-14-alkyloxy) methyl] derivs. 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	OECD Inherent Biodegradability: Zahn-Wellens/EMPA Test	12% [28 days] - Not readily 87% [28 days] - Readily
	OECD Ready Biodegradability - Closed Bottle Test	9% [29 days] - Not readily

Product/ingredient name	Aquatic half-life	Photolysis	
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 oxirane, mono[(C12-14-alkyloxy) methyl] derivs. 12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine			Not readily
			Readily
			Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	2.64 - 3.78	31	Low
dibutyl phthalate	4.46	165.96	Low
4-nonylphenol, branched	5.4	740	High
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 - 263	Low
12-hydroxyoctadecanoic acid, reaction products with 1,3-benzenedimethanamine and hexamethylenediamine	6.01	-	High

12.4 Mobility in soil

Product/ingredient name	logK _{oc}	K _{oc}
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	3.26	1800
dibutyl phthalate	3.14	1381.63
4,4'-isopropylidenediphenol	3.16	1436.23

Mobility : No known data available in our database.

SECTION 12: Ecological information

Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods







The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

Transport may take place according to national regulation NZS for transport by road and train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
NZS Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	Hazchem code •3Z
IMDG Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F
IATA Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

PG* : Packing group

Env.* : Environmental hazards

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification

SKIN IRRITATION - Category 2

SERIOUS EYE DAMAGE - Category 1

SKIN SENSITISATION - Category 1

REPRODUCTIVE TOXICITY - Category 1

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1

Safety, health and environmental regulations specific for the product :

SECTION 15: Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients).

HSNO Group Standard : HSR002670

HSNO Group Standard assigned are based upon the GHS Classification.

SECTION 16: Other information

🔹 Indicates information that has changed from previously issued version.

Classification	Justification
SKIN IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
REPRODUCTIVE TOXICITY - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	Calculation method

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.